

CNS 1500 Plus LCD

CONVECTORS

PRODUCT-NO.: 205856

Perfect combination of heat and good looks Even in small or cramped rooms, you shouldn't have to miss out on cosy warmth. This heater not only reliably takes care of all that but looks really good too. Its high quality appearance ensures that the convector fits well into virtually any living space. But it's not just the attractive design that will impress you. The functionality will too.

Efficient temperature delivery The wall mounted appliance heats up the indoor air in your home evenly, silently and to precisely the right temperature. The easy-to-read display makes it exceptionally user friendly. Here, you can select your preferred temperature and program any time control settings you may require. So you can be sure that the convector only heats up the room when you actually want it to.

The main features

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

Quiet, even temperature distribution

Attractively designed metal casing

Operating controls with illuminated LCD screen

Weekly timer, frost protection and open window detection

Self-learning room temperature control: automatic calculation of the preheat time in timer mode

ON/OFF switch and overheating protection

**CNS 500 Plus LCD**

Product-No.: 205853

**CNS 750 Plus LCD**

Product-No.: 205854

**CNS 1000 Plus LCD**

Product-No.: 205855

**CNS 2000 Plus LCD**

Product-No.: 205857

**CNS 2500 Plus LCD**

Product-No.: 205858

**CNS 3000 Plus LCD**

Product-No.: 205859



Type	CNS 500 Plus LCD	CNS 750 Plus LCD	CNS 1000 Plus LCD
Part no.	205853	205854	205855

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	230 V	230 V	230 V
Rated current	2,2 A	3,3 A	4,3 A
Connected load	0,5 kW	0,75 kW	1,0 kW
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	white	white	white
Setting range	5-30 °C	5-30 °C	5-30 °C
Height	450 mm	450 mm	450 mm
Width	348 mm	426 mm	426 mm
Depth	100 mm	100 mm	100 mm
Weight	4.00 kg	4.60 kg	4.90 kg



Type	CNS 1500 Plus LCD	CNS 2000 Plus LCD	CNS 2500 Plus LCD
Part no.	205856	205857	205858

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	230 V	230 V	230 V
Rated current	6,5 A	8,7 A	10,9 A
Connected load	1,5 kW	2,0 kW	2,5 kW
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	white	white	white
Setting range	5-30 °C	5-30 °C	5-30 °C
Height	450 mm	450 mm	450 mm
Width	582 mm	738 mm	894 mm
Depth	100 mm	100 mm	100 mm
Weight	6.00 kg	7.70 kg	9.20 kg



Type	CNS 3000 Plus LCD
Part no.	205859

Technical data

Power supply	1/N/PE ~ 230 V
Rated voltage	230 V
Rated current	13,0 A
Connected load	3,0 kW
IP rating	IP24
Protection class	I
Colour	white
Setting range	5-30 °C
Height	450 mm
Width	1050 mm
Depth	100 mm
Weight	10.90 kg

Depth including wall mounting bracket

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0909

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.