# CNS 2000 Plus LCD

CONVECTORS

Even in small or cramped rooms, you shouldn't have to miss out on cosy warmth. This heater not only reliably takes care of all that but looks really good too. Its high quality appearance ensures that the convector fits well into virtually any living space. But it's not just the attractive design that will impress you. The functionality will too.

The wall mounted appliance heats up the indoor air in your home evenly, silently and to precisely the right temperature. The easy-to-read display makes it exceptionally user friendly. Here, you can select your preferred temperature and program any time control settings you may require. So you can be sure that the convector only heats up the room when you actually want it to.

The main features

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

---

Quiet, even temperature distribution

Attractively designed metal casing

Operating controls with illuminated LCD screen

Weekly timer, frost protection and open window detection

Self-learning room temperature control: automatic calculation of the preheat time in timer mode


ON/OFF switch and overheating protection

Type	CNS 500 Plus LCD	CNS 750 Plus LCD	CNS 1000 Plus LCD
Part no.	205853	205854	205855
Wärmeleistung			
Rated heating output Pnom	0.50 kW	0.80 kW	1.00 kW
Minimum heating output (standard value) Pmin	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output Pmax,c	0.50 kW	0.80 kW	1.00 kW
Hilfsstromverbrauch			
Auxiliary power consumption with rated heating output elmax	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption with minimum heating output elmin	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption in standby mode elSB	0.00 kW	0.00 kW	0.00 kW
Art der Wärmeleistung/Raumtemperaturkontrolle			
Type of heating output/room temperature control: Single stage heating output, no room temperature control	-	-	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-	-	-
Type of heating output/room temperature control: With mechanic thermostat room temperature control	-	-	-
Type of heating output/room temperature control: With electronic room temperature control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus day timer	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus week timer	x	x	x
Sonstige Regelungsoptionen			
Other control options: Room temperature control, with presence detection	-	-	-
Other control options: Room temperature control, with open window detection	x	x	x
Other control options: With remote control option	-	-	-
Other control options: With adaptive control of heating startup	x	x	x
Other control options: With operating time limitation	-	-	-
Other control options: With black bulb sensor	-	-	-

Type	CNS 1500 Plus LCD	CNS 2000 Plus LCD	CNS 2500 Plus LCD
Part no.	205856	205857	205858

Wärmeleistung

	CNS 1500 Plus LCD	CNS 2000 Plus LCD	CNS 2500 Plus LCD
Rated heating output Pnom	1.50 kW	2.00 kW	2.50 kW
Minimum heating output (standard value) Pmin	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output Pmax,c	1.50 kW	2.00 kW	2.50 kW

Hilfsstromverbrauch

	CNS 1500 Plus LCD	CNS 2000 Plus LCD	CNS 2500 Plus LCD
Auxiliary power consumption with rated heating output elmax	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption with minimum heating output elmin	0.00 kW	0.00 kW	0.00 kW
Auxiliary power consumption in standby mode elSB	0.00 kW	0.00 kW	0.00 kW

Art der Wärmeleistung/Raumtemperaturkontrolle

	CNS 1500 Plus LCD	CNS 2000 Plus LCD	CNS 2500 Plus LCD
Type of heating output/room temperature control: Single stage heating output, no room temperature control	-	-	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-	-	-
Type of heating output/room temperature control: With mechanic thermostat room temperature control	-	-	-
Type of heating output/room temperature control: With electronic room temperature control	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus day timer	-	-	-
Type of heating output/room temperature control: Electronic room temperature control plus week timer	x	x	x

Sonstige Regelungsoptionen

	CNS 1500 Plus LCD	CNS 2000 Plus LCD	CNS 2500 Plus LCD
Other control options: Room temperature control, with presence detection	-	-	-
Other control options: Room temperature control, with open window detection	x	x	x
Other control options: With remote control option	-	-	-
Other control options: With adaptive control of heating startup	x	x	x
Other control options: With operating time limitation	-	-	-
Other control options: With black bulb sensor	-	-	-

Type	CNS 3000 Plus LCD
Part no.	205859

Wärmeleistung

Rated heating output Pnom	3.00 kW
Minimum heating output (standard value) Pmin	0.00 kW
Maximum continuous heating output Pmax,c	3.00 kW

Hilfsstromverbrauch

Auxiliary power consumption with rated heating output elmax	0.00 kW
Auxiliary power consumption with minimum heating output elmin	0.00 kW
Auxiliary power consumption in standby mode elSB	0.00 kW

Art der Wärmeleistung/Raumtemperaturkontrolle

Type of heating output/room temperature control: Single stage heating output, no room temperature control	-
Type of heating output/room temperature control: Two or more manually adjustable stages, no room temperature control	-
Type of heating output/room temperature control: With mechanic thermostat room temperature control	-
Type of heating output/room temperature control: With electronic room temperature control	-
Type of heating output/room temperature control: Electronic room temperature control plus day timer	-
Type of heating output/room temperature control: Electronic room temperature control plus week timer	x

Sonstige Regelungsoptionen

Other control options: Room temperature control, with presence detection	-
Other control options: Room temperature control, with open window detection	x
Other control options: With remote control option	-
Other control options: With adaptive control of heating startup	x
Other control options: With operating time limitation	-
Other control options: With black bulb sensor	-

Depth including wall mounting bracket

Contact information

You have questions? We appreciate to help you:
SALES HOTLINE
+91 2067 48 0928
SERVICE HOTLINE
+91 2067 48 0909

Write an email to **sales@stiebel-eltron.in**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that
are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with
obtaining the agreement of the respective power supply utility required for the appliance
installation.