

DDP 6 EC (IN)

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 207632

The main features

Instantaneous water heater with electronic closed-loop control

Also supplies several draw-off points with hot water

Space saving installation due to compact design

Durable copper tank, resistant to high pressure and heat

Durable, corrosion-free heating element made of copper

Reliable protection against scalding and overheating thanks to thermal circuit breaker

High level of protection against electric shocks thanks to residual current device (ELCB)

Protection rating IP 25 – splashproof





Type	DDP 6 EC (IN)
Part no.	207632

Technical data

Cold water connection	1/2 inch
Electrical fuse protection	ELCB
Rated output	6,000 W
Electrical connection	1/N/PE~220-240 V
Rated voltage	220-240 V
Rated current	27.3-29.6 A
Display	without
Heating element	Copper tubular
Type	Closed outlet
Automatic flow switch	true
Heating material	Copper
Temperature control	Output control
Anti-scalding protection	Thermostat with manual reset
Colour	white
IP rating	IP25
Shutdown value	1.4 l/min
Starting flow rate	1.8 l/min
Depth	93 mm
Height	177 mm
Width	204 mm

Weight

1.5 kg

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0909

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.